

Anionic Slow Setting Emulsion

EMULSIONS

2018 EDITION

PRODUCT DESCRIPTION

- Anionic Slow Setting (ASS) Emulsion is an anionic slow setting bitumen emulsion formulated for tackcoat, enrichment and general road work.
- ASS is available in bulk supply or in 20 litre and 205 litre containers.

TYPICAL APPLICATIONS INCLUDE

- Protection of cuttings and embankments from erosion.
- Prevent running on the slopes in dam embankments.
- Road enrichment.
- Dust suppression of roads and work areas.
- Grass seed germination.

PREPARATION AND APPLICATION

- The ASS emulsion can be diluted up to 50/50 with water, and the diluted emulsion sprayed at a rate of about 1.5 - 2.5 L/m².
- ASS can be sprayed with conventional agricultural spray bars. Apparatus should be washed with water immediately after use. Mineral turps or diesel can be used to clean any residual bitumen.
- Rejuvenation of road surfaces use 50/50 dilutions at approximately 0.6 L/m² dependant on surface conditions.
- For dust suppression, dilute 1 part ASS with 10 parts water in a water cart, and use multiple passes of the spray bar until satisfactory penetration is achieved. Recoat as necessary according to traffic conditions.
- When diluting, always add water to emulsion (not emulsion to water) and do not splash feed. Feed from bottom.
- Dilute only what is required at the time of application. Do not store diluted emulsion.
- Drums should be stored off the ground and preferably undercover.



Boral website:

Visit the Boral website for the full range of Boral products: www.boral.com.au

Asphalt information:

For asphalt news and information visit: www.boral.com.au/asphalt

For asphalt locations around Australia go to: www.boral.com.au/locations

Contact us:

At Boral we are committed to excellence in service so for further information please contact:

NSW (02) 8801 2000
VIC 1300 132 964
QLD (07) 3268 8011
SA (08) 8425 0400
WA (08) 9458 0400

or visit: www.boral.com.au/contact